

TUFFBUOY

Safety Barrier Floats

TUFFBUOY safety barrier floats are attached in a series to warn or restrict boaters or swimmers from dangerous areas such as spillways, dams, marina's and beaches.

TUFFBUOY floats can be attached using a continuous length of cable (type PT) or using individual cable sections between each float (type SE). Typical spacing varies from 15' to 25' between float units.

Specifications:

- Outer shell: Seamless ultra-strong polyethylene shell with UV inhibitors. No ABS. Min 0.140 thickness.
- Buoyancy: Unsinkable even if punctured. Completely foam filled Coast Guard approved foam. 2lb density.
- Suitable for use to -40°F/C.

Options:

- USCG retroreflective tape
- Alternate colors including Canadian Coast Guard Yellow.
- Owner or agency graphics.
- Stainless steel hardware.

Suggested Hardware:

- Cable, cable clamps, anchor chain, anchor block, cable thimble, cable swivel.



Type – SE

Threaded rod thru float
Swivel eye nuts both ends

Type – PT

Steel or Plastic pipe through float

Part Number	Barrier Style	Dia. and Length	Type	Description – Standard colors are international orange or white (specify color when ordering)	Submerged Buoyancy	Net Wt.
T1313-SE		13" round	SE	1/2" dia steel rod thru center with galvanized swivel eye nut both ends.	35 lbs	5 lbs
T1818-SE		18" round			95 lbs	14 lbs
T2424-SE		24" round			240 lbs	20 lbs
T1313-PT		13" round	PT	1/2" sch. 40 PVC pipe thru on 13" round. 1" sch. 40 galvanized pipe thru in 18" & 24" round.	35 lbs	5 lbs
T1818-PT		18" round			95 lbs	14 lbs
T2424-PT		24" round			240 lbs	20 lbs
T1318-SE		13" x 18"	SE	1/2" dia steel rod thru center with galvanized swivel eye nut both ends.	55 lbs	10 lbs
T1830-SE		18" x 30"			200 lbs	25 lbs
T2436-SE		24" x 36"			385 lbs	55 lbs
T2445-SE		24" x 45"				70 lbs
T3648-SE		36" x 48"			Special internal components	
T1318-PT		13" x 18"	PT	1/2" sch. 40 PVC pipe thru on 13" unit. 1" sch. 40 galvanized pipe thru.	55 lbs	10 lbs
T1830-PT		18" x 30"			200 lbs	25 lbs
T2436-PT		24" x 36"			385 lbs	55 lbs
T2445-PT		24" x 45"				70 lbs
T3648-PT		36" x 48"			Special internal components	